

INFRACOM®

Dual Interpreter Console DOL7/2E

Article No.: 04.2541.07



Description

The dual interpreter Console DOL7/2 for use by two interpreters is designed for the transmission of 1+6 channels (6 languages). DOL7/2 is interconnected to the control console and the next interpreter console by Daisy-chain technology.

The control panel is divided into clearly organized function-oriented sections: monitoring - speaking - special functions. The controls are designed in a user-friendly manner and are easy to operate.

Via the two "Monitoring" function sections, one may preselect an interpretation channel using the 6-digit rotary switch. The interpreter can choose between this interpretation channel and the ORIGINAL (floor) channel using the RELAIS toggle switch. Volume, bass, and treble are individually adjustable via separate controls.

Features

- control panel for two interpreters
- 1+6 channels
- interconnection using single-cable technology
- A/B/C outgoing channel selection
- processor-controlled functions
- display of the output channel and the language complying to ISO639

Technical Data

Complies with the standards IEC914 and DIN56924 Part 1 "Booths for Simultaneous Interpretation"

- Plug standard : A36K
- Permanently attached connection cable 3.5m and socket A36K standard for hooking up to the control console,
- 3.5mm jack plug for standard headphones
- 2 D7-CB connector sockets for headphones or electret headset
- 2 D5-BS connector sockets for electret microphone TM55/18
- Processor-controlled
- Rotary switch to program all individual settings
- Microphone preamplifier with limiter; balanced output +6dBV, frequency response 125Hz-15kHz,
- S/N ratio >60dB(A),
- Harmonic distortion <1 %
- LC-Display consisting of 2x16 characters for displaying the number, language and state of the output channels
- Monitor amplifier for headphone, separate controls for bass, treble, volume,
- Frequency response 100Hz - 20kHz,
- S/N ratio >70dB(A),
- Harmonic distortion <0.5%
- Three locking modes regarding the outgoing channel interlocking function

- Robust plastic lower housing, colour: black
- Operation panel: aluminium, "silver" anodized.
- Dimensions: 305 x 96 x 175mm
- Weight with cable: approx. 1.9kg (with cable)

Accessories

(not included in delivery)

- K45/6 Dynamic Headphone
- PMX60 Dynamic Conference Headphone with neckband
- K15 Conference Headphone
- TM55/18 Interpreter Microphone, electret
- HS394 Lightweight Interpreter Headset
- HS460 Interpreter Headset
- A36K-5 extension cable 5m
- A36K-10 extension cable 10m
- KAD03 Aluminium transport box