

DDol

DIGIMIC Digital Interpreter Console with 8 audio channels

Article no.: 05.0700



Description

DIGIMIC's DDol digital Interpreter Console for one interpreter and up to 8 audio channels (OR + 7 languages). It's clearly arranged controls, its large, bright display and the illuminated buttons allow straight and intuitive operation. Up to 3 selectable output channels and 5 preset monitoring languages are just as self-understood. Additional separate call channels are provided to technical team or the chairperson. All common (mono and stereo) headphones can easily be connected to the console and in combination with various microphone types or combined headsets it guarantees maximum comfort for the interpreter. The interpreter console is divided into 3 sections:

Speaking section

- Three outgoing channels (A/B/C)
- Microphone ON/ OFF button
- Mute button to mute the active microphone temporarily
- Clear indication of active and occupied channels

Listening and relay section

- 5 preset relay channels
- separate floor key
- Relay interpretation quality indicator

Monitoring section

- Loudspeaker with channel selector to monitor all languages
- All loudspeakers within one booth will be muted automatically when a DDol in the booth goes live

Additional Features

- Operator and/ or chairperson call
- Auto Relay, Auto Floor
- Various take-over modes programmable
- "Hearing guard" LED to indicate high headphone volume level
- Assistance call and "Speak slow" function in conjunction with brählerOS software

Technical Data

Complies with the standards IEC914 and IEC2603.2

- OR + 7 channels
- Sample rate 48kHz
- Resolution 24 BIT
- Frequency response: 20 - 20,000 Hz
- Latency end to end 1.5 ms
- LC-Display, 2 x 56 characters, backlit

Connections

- PREVIOUS (D9) for interconnection
- NEXT (D9) for interconnection
- Microphone TM58/6 or TMD01 (Minicon socket) lockable
- Headphones (3.5/6.3 mm jack)
- Electret Headset 8-pin socket (DIN)

Housing

- Lower part: robust plastic, black
- Operation panel: aluminium, "silver" anodized
- WxHxD: (305 x 96 x 175) mm
- Weight: 1.5 kg

Accessories

(not included in delivery)

Supported Central Control Units

- DCen
Article no.: 05.0010

Microphones/Headsets

- TMD/01-S2 with 2 goosenecks
Article no.: 01.0701.S2
- TMD/CL
Article no.: 01.0750
(microphones available in different lengths)
- HS460 Interpreter Headset
Article no.: 03.5550

Other Components

- DExt Extension Power Supply
Article no.: 05.0020

Software

brählerOS to manage DIGIMIC hardware. Easy configuration of all interpreter units from a single point.
Article no.: OS.0100, OS.0100 etc.