

## DIGIMIC CS Channel Selector

Article no.: 05.0270



### Description

The DIGIMIC CS is the compact and inexpensive solution for listening to multi-channel audio signals within a conference.

The conference delegates can select from up to 32 language channels. Channel number and volume can be monitored via a bright illuminated display and controlled by 4 buttons (Vol up/down and Channel up/down).

Numerous DIGIMIC CS units can be connected via the DIGIMIC CSX4 language selector central unit. The CSX4 has four outputs - up to 40 DIGIMIC CS units are possible per output. In addition, several CSX4 units can be connected in series, allowing an almost infinite number of units to be combined. A cable length of up to 100m is possible between the individual units.

Due to its small size, the DIGIMIC CS can be easily integrated into tables or armrests. The channel selectors are easily connected using the CAT sockets at the back of the unit.

The DIGIMIC CS has a standard headphone socket (3.5mm) which allows the connection and use of any common mono or stereo headphones.

### Features

#### Attributes

- Compact installation dimensions
- 2 buttons for volume control
- 2 buttons for channel selection
- Illuminated LCD display
- Standard headphone jack

#### Audio Features

- High quality digital audio signal
- Sample rate: 48 kHz
- Frequency response: 20-20.000Hz
- Floor + 31 language channels

#### Connectors

- 2x RJ45 DIGIMIC BUS
- 3.5mm jack socket

#### Case

- Front panel: aluminium, painted
- Rear cover: bare aluminium
- Dimensions: H x W x D
- 102.5mm x 61mm x 41mm
- Installation depth with plug: 97mm
- Weight: approx. 130g

### System components

#### Supported central units

- DCen32  
Article no.: 05.0050
- CSX4  
Article no.: 05.0070